

ITEM	ITEM DESCRIPTION	WEIGHT		PART-No.
		(kg)	(lb)	
01	TOP SUB	10.15	22.38	TMS40-01
02	FEED TUBE RETAINER PIN	0.08	0.17	TMS40-02
03	CHECK VALVE	0.03	0.07	TMS40-03
04	CHECK VALVE O'RING	0.01	0.02	TMS40-04
05	TOP SUB O'RING	0.00	0.00	TMS40-05
06	CHECK VALVE GUIDE	0.27	0.59	TMS40-06
07	FEED TUBE	0.64	1.42	TMS40-07
08	CHOKE SET	0.00	0.01	TMS40-08
09	PISTON	7.06	15.56	TMS40-09
10	GUIDE SLEEVE O'RING (2 PCS)	0.00	0.00	TMS40-10
11	GUIDE SLEEVE	1.82	4.01	TMS40-11
12	BIT RETAINING RING	0.25	0.55	TMS40-12
13	BIT RET. RING O'RING	0.00	0.00	TMS40-13
14	WEAR SLEEVE	14.95	32.96	TMS40-14
15	PISTON RETAINER RING	0.02	0.05	TMS40-15
16	DRIVE SUB	3.16	6.97	TMS40-16
17	WEAR SLEEVE O'RING	0.00	0.00	TMS40-17
18	DRIVE SUB O'RING	0.00	0.00	TMS40-18
19	CHECK VALVE BEARING	0.06	0.13	TMS40-19

HAMMER SPECIFICATIONS

LENGTH (WITHOUT BIT)	WEIGHT (WITHOUT BIT)	EXTERNAL DIAMETER	BIT SHANK	BIT RANGE	CONNECTION THREAD
987 mm 39 in	39 kg 86 Lb	98 mm 3.86 in	MS-40	Ø 4.1/8" - Ø 5.1/2"	API 2.3/8" IF (BOX)
WORKING PRESSURE	IMPACTE RATE	RECOMMENDED ROTATION SPEED		AIR CONSUPTION	
150 – 350 PSI 10 – 23,5 BAR	21 Hz	25 – 85 rpm		190 – 465 CFM	