

ITEM	ITEM DESCRIPTION:	WEIGHT (KG)	PART CODE
01	WEAR SLEEVE	7.375	TSCR3-01
02	TOP SUB	3.099	TSCR3-02
03	PISTON	4.940	TSCR3-03
04	AIR DISTRIBUTOR	0.925	TSCR3-04
05	CYLINDER	1.159	TSCR3-05
06	CHECK VALVE	0.177	TSCR3-06
07	STOP RING	0.069	TSCR3-07
08	CHECK VALVE SPRING	0.007	TSCR3-08
09	DRIVE SUB	1.764	TSCR3-09
10	GUIDED SLEEVE	0.923	TSCR3-10
11	STOP PIN SPRING	0.001	TSCR3-11
12	STOP PIN	0.004	TSCR3-12
13	STOPPER	0.001	TSCR3-13
14	BIT PIN	0.017	TSCR3-14
15	O'RING PARKER 2-231	0.002	TSCR3-15
16	O'RING PARKER 2-229	0.002	TSCR3-16

HAMMER SPECIFICATIONS

LENGTH (WITHOUT BIT)	WEIGHT (WITHOUT BIT)	EXTERNAL DIAMETER	BIT SHANK	BIT RANGE	CONNECTION THREAD
794 mm 31.3 in	24 Kg	Ø 80 mm Ø 3.15 in	CIR-90	Ø 3.3/4" - 4.3/4"	API 2.3/8" REG (BOX)
WORKING PRESSURE	IMPACTE RATE	RECOMMENDED ROTATION SPEED	AIR CONSUPTION		
175 – 360 PSI 11,7 – 24 BAR	20 Hz	15 – 25 rpm	750 – 1400 CFM		