

ITEM	ITEM DESCRIPTION	WEIGHT		PART-No.
		(kg)	(lb)	
01	WEAR SLEEVE	66.47	146.54	TQL8-01
02	TOP SUB	36.73	80.97	TQL8-02
03	PISTON	44.78	98.72	TQL8-03
04	AIR DISTRIBUTOR	6.25	13.78	TQL8-04
05	INTERNAL CYLINDER	7.29	16.07	TQL8-05
06	CHECK VALVE	0.59	1.30	TQL8-06
07	CHECK VALVE SPRING	0.12	0.25	TQL8-07
08	CONDUIT	0.14	0.31	TQL8-08
09	BIT RETAINING RING	1.21	2.67	TQL8-09
10	DRIVE SUB	13.79	30.40	TQL8-10
11	GUIDED SLEEVE	10.71	23.61	TQL8-11
12	TOP SUB O'RING	0.00	0.01	TQL8-12
13	BIT RET. RING O'RING	0.01	0.02	TQL8-13

HAMMER SPECIFICATIONS

LENGTH (WITHOUT BIT)	WEIGHT (WITHOUT BIT)	EXTERNAL DIAMETER	BIT SHANK	BIT RANGE	CONNECTION THREAD
1.228 mm 48.35 in	188 kg 414.5 lb	185 mm 7.25 in	QL – 80	Ø 8" - 10"	API 4.1/2" REG (PIN)
WORKING PRESSURE	IMPACTE RATE	RECOMMENDED ROTATION SPEED	AIR CONSUMPTION		
150 – 350 PSI 10 – 23,5 BAR	20 Hz	10 – 40 rpm	530 – 1200 CFM		