

TIGER HD5 - DTH Hammer

ITEM	ITEM DESCRIPTION	WEIGHT		PART-No.
		(kg)	(lb)	
01	TOP SUB	10.99	24.23	THD5-01
02	TOP SUB O'RING	0.00	0.01	THD5-02
03	CHECK VALVE	0.26	0.56	THD5-03
05	CHECK VALVE SPRING	0.02	0.05	THD5-05
06	MAKE UP RING	0.21	0.46	THD5-06
07	SPRING WASHER	0.08	0.18	THD5-07
08	AIR DISTRIBUTOR	4.04	8.90	THD5-08
09	AIR DIST. O'RING	0.00	0.00	THD5-09
10	PLUG	0.00	0.01	THD5-10
11	WEAR SLEEVE	26.35	58.09	THD5-11
12	CYLINDER	3.82	8.42	THD5-12
13	PISTON	12.95	28.54	THD5-13
15	SNAP RING	0.25	0.55	THD5-15
16	BIT RETAINING RING	0.40	0.89	THD5-16
17	BIT RET. RING O'RING	0.00	0.00	THD5-17
18	DRIVE SUB	4.21	9.28	THD5-18

HAMMER SPECIFICATIONS

LENGTH (WITHOUT BIT)	WEIGHT (WITHOUT BIT)	EXTERNAL DIAMETER	BIT SHANK	BIT RANGE	CONNECTION THREAD
1073 mm 42.2 in	64 kg 141.1 lb	115.5 mm 4.55 in	DHD – 350	Ø 5.1/8" - Ø 6.1/2"	API 2. 3/8" IF (BOX)
WORKING PRESSURE	IMPACTE RATE	RECOMMENDED ROTATION SPEED		AIR CONSUPTION	
150 – 300 PSI 10,3 – 20,7 BAR	25 Hz	20 – 35 rpm		300 – 750 CFM	