



ITEM	ITEM DESCRIPTION	WEIGHT		PART-No.
		(kg)	(lb)	
01	WEAR SLEEVE	35.16	77.51	TQL6-01
02	TOP SUB	21.46	47.31	TQL6-02
03	PISTON	25.64	56.53	TQL6-03
04	AIR DISTRIBUTOR	3.47	7.65	TQL6-04
05	INTERNAL CYLINDER	5.13	11.31	TQL6-05
06	CHECK VALVE	0.505	1.11	TQL6-06
07	CHECK VALVE SPRING	0.058	0.13	TQL6-07
08	CONDUIT	0.007	0.02	TQL6-08
09	BIT RETAINING RING	0.67	1.48	TQL6-09
10	DRIVE SUB	7.31	16.12	TQL6-10
11	GUIDED SLEEVE	5.85	12.90	TQL6-11
12	TOP SUB O'RING	0.003	0.01	TQL6-12
13	BIT RET. RING O'RING	0.004	0.01	TQL6-13

HAMMER SPECIFICATIONS

LENGTH (WITHOUT BIT)	WEIGHT (WITHOUT BIT)	EXTERNAL DIAMETER	BIT SHANK	BIT RANGE	CONNECTION THREAD
1.092 mm 42.3 in	105 kg 231.5 lb	147 mm 5.79 in	QL - 60	Ø 6. 1/8" - 8.1/2"	API 3.1/2" REG (PIN)
WORKING PRESSURE	IMPACTE RATE	RECOMMENDED ROTATION SPEED		AIR CONSUMPTION	
150 - 350 PSI 10 - 23,5 BAR	23 Hz	15 - 60 rpm		353 - 1007 CFM	