

ITEM	ITEM DESCRIPTION	WEIGHT		PART-No.
		(kg)	(lb)	
01	TOP SUB	4.41	9.72	TBR3-01
02	TOP SUB O'RING	0.00	0.00	TBR3-02
03	VALVE SEAL	0.02	0.04	TBR3-03
04	CHECK VALVE	0.11	0.24	TBR3-04
05	CHECK VALVE SPRING	0.01	0.02	TBR3-05
06	VALVE GUIDE	0.62	1.36	TBR3-06
07	PLUG	0.00	0.00	TBR3-07
08	CHOKE SET	0.03	0.07	TBR3-08
09	VALVE WASHER	0.04	0.08	TBR3-09
10	AIR DISTRIBUTOR	1.18	2.60	TBR3-10
11	INTERNAL CYLINDER	1.90	4.19	TBR3-11
12	PISTON	3.35	7.38	TBR3-12
13	GUIDED SLEEVE	0.64	1.41	TBR3-13
14	WEAR SLEEVE	7.65	16.86	TBR3-14
15	STOP RING	0.36	0.79	TBR3-15
16	BIT RETAINING RING	0.26	0.57	TBR3-16
17	SEALING RING	0.01	0.01	TBR3-17
18	DRIVE SUB	1.78	3.92	TBR3-18
19	BIT RET. RING O'RING	0.00	0.00	TBR3-19

## HAMMER SPECIFICATIONS

LENGTH (WITHOUT BIT)	WEIGHT (WITHOUT BIT)	EXTERNAL DIAMETER	BIT SHANK	BIT RANGE	CONNECTION THREAD
768 mm 30,3 in	22 Kg 48.5 lb	Ø 82 mm Ø 3.1/4"	BULROCK 3	Ø 90 – Ø 110 mm Ø 3.1/2" - Ø 4.3/8"	API 2 3/8" REG (PIN)
WORKING PRESSURE	IMPACTE RATE	RECOMMENDED ROTATION SPEED		AIR CONSUPTION	
100 – 254 PSI 6,9 – 17 BAR	25 Hz	25 – 40 rpm		140 – 285 CFM	