

ITEM	ITEM DESCRIPTION	WEIGHT		PART-No.
		(kg)	(lb)	
01	TOP SUB	13.30	29.32	THD4-01
02	TOP SUB O'RING	0.00	0.00	THD4-02
03	VALVE SEAT	0.56	1.23	THD4-03
04	VALVE SEAT O'RING	0.00	0.00	THD4-04
05	CHECK VALVE	0.10	0.21	THD4-05
06	PLUG	0.00	0.00	THD4-06
07	CHECK VALVE SPRING	0.02	0.04	THD4-07
08	GUIDE TUBE	0.12	0.27	THD4-08
09	PISTON	9.04	19.93	THD4-09
10	DRIVE SUB	2.56	5.63	THD4-10
11	BIT RETAINING RING	0.39	0.85	THD4-11
12	SNAP RING	0.10	0.22	THD4-12
13	WEAR SLEEVE	0.15	0.32	THD4-13
14	RETAINING WASHER	1.21	2.67	THD4-14
15	BIT RET. RING O'RING	0.02	0.04	THD4-15

HAMMER SPECIFICATIONS

LENGTH (WITHOUT BIT)	WEIGHT (WITHOUT BIT)	EXTERNAL DIAMETER	BIT SHANK	BIT RANGE	CONNECTION THREAD
1051 mm 41.4 in	38,5 Kg 84.8 Lb	92 mm 3.62 in	DHD - 340	Ø 4. 1/8" - Ø 5. 1/2"	API 2 3/8" REG (BOX)
WORKING PRESSURE	IMPACTE RATE	RECOMMENDED ROTATION SPEED		AIR CONSUPTION	
82 - 350 PSI 5,5 - 23,5 BAR	27 Hz	25 - 40 rpm		182 - 780 CFM	